SCANNED, #24



FIG. 1


F_n
F_{n+1}
S_2
S_0
S_1
S_2
S_0
160
161
162
164
166
171
0 1 2 3 4 5 • • A B C D E F
SYNC

FIG. 4A


Cu
HEAD
END
Ru #1
USER
1
Ru #2
USER
2
170
162
164
166
GB
171
173
178
180
167
169
172
168
174
176
182
O
X
Y

FIG. 4B


Cu
HEAD END
Ru #1
NEAREST
USER
Ru #128
FURTHEST
USER
FRAME
1
FRAME
2
170
99
100
196
190
192
193
102
198
172
196
109
103
108
138
110
106
111
112
113
114
T
116

FIG. 5


Cu
HEAD END
Ru #1
NEAREST
USER
Ru #128
FURTHEST
USER
Need PRELIM
FRAME
#1
INTERVAL
= T_F
T_{CU}
T_{NEAR}
T_{FAR}
170
132
137
116
135
196
90
139
192
94
120
196
99
118
141
122
196
196
136
134
130
127
126
125
123
128
131
124
106
133

FIG. 4

GENERAL RANGING PROCESS

FIG. ~~7A~~ 5A




FROM FIG. 7A
5A
194
CU MONITORS GAP DURING PLURALITY OF SIGNATURE SEQUENCE FRAMES IN THE AUTHENTICATION INTERVAL AND PERFORMS CORRELATIONS DURING EACH GAP.
196/197
CU COUNTS THE NUMBER OF GAPS IN AUTHENTICATION INTERVAL THAT HAVE ACTIVITY AND COMPARES THAT NUMBER TO THE TOTAL NUMBER OF FRAMES IN THE AUTHENTICATION INTERVAL TO DETERMINE IF THE 50% ACTIVITY LEVEL LIMIT HAS BEEN EXCEEDED.
GREATER THAN 50% ACTIVITY
204
CU BROADCASTS MESSAGE TO ALL RU'S INSTRUCTING ALL RU'S ATTEMPTING SYNCHRONIZATION TO EXECUTE THEIR COLLISION RESOLUTION PROTOCOLS.
50% ACTIVITY DETECTED
199
198
CU IDENTIFIES RU FROM SIGNATURE AND BROADCASTS IDENTITY SO DETERMINED.
206
EACH RU ATTEMPTING TO SYNCHRONIZE EXECUTES A RANDOM DECISION WHETHER TO CONTINUE ATTEMPTING TO SYNCHRONIZE OR TO STOP, WITH A 50% PROBABILITY OF EITHER OUTCOME.
200
RU WITH IDENTITY BROADCAST BY CU RECOGNIZES ITS IDENTITY IN BROADCAST AND ENTERS FINE TUNING MODE.
208
202
CU INSTRUCTS RU ON HOW TO ADJUST ITS DELAY IN ORDER TO CENTER THE CORRELATION PEAK IN THE MIDDLE OF THE GAP/GUARDBAND.
RU'S THAT HAVE DECIDED TO CONTINUE RETRANSMIT THEIR SIGNATURE WITH THE SAME TIMING AS WAS USED ON THE LAST ITERATION
TO FIG. 7B 5C

5B

FIG. 7B


FROM
210
CU MONITOR GAPS OF AUTHENTICATION INTERVAL FOR ACTIVITY
NO ACTIVITY
ONLY ONE RU IN GAP
MORE THAN ONE RU IN GAP
212
CU BROADCASTS A MESSAGE INSTRUCTING ALL RU'S TO GO BACK TO PREVIOUS STAGE AND RE-EXECUTE THEIR DECISIONS TO CONTINUE OR DISCONTINUE RANGING PROCESS
AUTHENTICATE AND FINE TUNE
222
TO BLOCK 204
220
214
RU'S RE-EXECUTE DECISION TO CONTINUE OR STOP AND RETRANSMIT THEIR SIGNATURES WITH SAME DELAY TIMING USED ON PREVIOUS ITERATION
216
NO
MORE THAN 10 ATTEMPTS?
YES
218
RETURN TO BLOCK 180

FIG. 7C



6

FIG. 8

DEAD RECKONING RE-SYNC



FIG. 9

PRECURSOR EMBODIMENT

DIGITAL MODEM BLOCK DIAGRAM



MODEM RU RECEIVE 8

FIG. 19


F4
F0
299
372
BIT CLK
377
CLK
RST
BIT COUNTER
CE
376
377
BIT CLOCK
374
370
CLK
RST
BYTE COUNTER
CE
302
BYTE CLOCK
376
CLK
RST
FRM COUNTER
CE
299'
F0
326
Td ADD
F'0
381
499
TIME DIVISION MULTIPLEXED DATA STREAM
301
310
DATA IN
SERIAL IN PARALLEL OUT SHIFT REGISTER
CLK
BIT CLOCK
377
Td FROM CPU
9
316
314
REGISTER
CLK
BYTE CLOCK
302
321
299'
F0
PAGE POINTER
RESET
366
362
WRITE POINTER
322
MUX
CHIP CLOCK
READ POINTER
324
364
348
RESET
F!0
381
PAGE POINTER
323
368
318
9
300
WR DATA
ADR
RAM
CTL
RD DATA
358
9
RD/WR
MUX
TRIBIT SELECT
356
3
354
360
TIME BASE GENERATOR (PLL)
312
XTAL OSC
351
350
TO FEC ENCODER OR CDMA MUX/BUFFER

FIG. 12


T1
CHI CLK (Fs)
Tc
T2
BIT CLK (16/7 Fs)
Tb
T3
BYTE CLK (2/7 Fs)
Ts
T4
T5
16xFs
T6
2xFs
T7
Fs
Tc
T8
16/7 Fs
Tb
T9
Ts

FIG. 13



15

FIG. 17



11

FIG. 18



FIG. 14



FIG. 15



FIG. 16


PAGE 1
MEMORY 300
SYMBOL 3
SYMBOL 2
SYMBOL 1
144
ADDR
LOCATIONS
TB1
TB2
TB3
TIME SLOT 1 /
CHANNEL
1 = 9 BITS
3 BITS
3 BITS
3 BITS

FIG. ~~20~~ 16



PREFERRED TRELLIS ENCODER

FIG. 42

17

MAPPING FOR FALL-BACK MODE - LSB'S



21

FIG. 43



18

FIG. 21

CODE	INPHASE	QUADRATURE	
0000	111	111	= -1 - j
0001	001	111	= 1 - j
0010	001	001	= 1+j
0011	111	001	= -1+j
0100	011	111	= 3 - j
0101	001	011	= 1+ 3*j
0110	101	001	= -3 + j
0111	111	101	= -1 - 3* j
1000	011	011	=+3 + 3*j
1001	101	011	= -3 + 3*j
1010	101	101	= -3 - 3* j
1011	011	101	= 3 - 3* j
403 1100	111	011	= -1+ 3* j
1101	101	111	= -3 - j
1110	001	101	= 1 - 3* j
1111	011	001	= 3 + j

19

FIG. 22



20A

FIG. ~~23~~A



20B

FIG. ~~23~~B

LSBs y1 y0	PHASE	1+jQ
00	0	3-j
01	90	1+j3
10	180	-3+j
11	-90	-1-j3

MSBs y3 y2	PHASE difference (2nd-1st symbol)	1+jQ WHEN LSB=00	1+jQ WHEN LSB=01	1+jQ WHEN LSB=10	1+jQ WHEN LSB=11
00	0	3-j	1+j3	-3+j	-1-j3
01	90	1+j3	-3+j	-1-j3	3-j
10	180	-3+j	-1-j3	3-j	1+j3
11	-90	-1-j3	3-j	1+j3	-3+j

LSB & MSB FALLBACK MODE MAPPINGS

FIG. ~~44~~ 22


411
409
413
408
144
I
Q
453
BIT PARSING
RESULT OR "CHIPS OUT" ARRAY
451
408
410
OPTIONAL FILTER
REAL
429
443
421
431
427
COS
417
425
LOCAL OSC.
412
427
COS
439
90° PHASE SHIFT
445
419
437
SIN
OPTIONAL FILTER
IMAG
423
433
435
441
410

FIG. 24


AMPL
8
7
6
5
4
3
2
1
0
TIME

FIG. 25



EMBODIMENT 1
CARRIER RECOVERY

FIG. 35

25



EMBODIMENT 2 CARRIER RECOVERY

FIG. 36

26


RU PERFORMS RANGING AND ACHIEVES FRAME SYNCHRONIZATION
1500
RU PERFORMS TRAINING TO SET THE COEFFICIENTS OF ITS FILTERS FOR PROPER EQUALIZATION
1502
1504
IDLE ?
YES
1505
NO
RU REQUESTS BANDWIDTH FROM CU USING ASK MOD
1506
CU AWARDS BANDWIDTH IN THE FORM OF ONE OR MORE TIMESLOTS ASSIGNED TO THIS RU
1508
RU SENDS KNOWN PREAMBLE DATA IN ASSIGNED TIMESLOTS
1510
CU DETECTS PHASE AND AMPL. ERROR FOR THIS RU FROM PREAMBLE DATA IN ASSIGNED TS AND STORES IN MEMORY LOCATION MAPPED TO THIS RU
1512
AS PAYLOAD DATA FROM THIS RU IS RECEIVED, CU CPU LOOKS UP PHASE AND AMPLITUDE ERROR FOR THIS RU AND SENDS TO CONTROL CIRCUITRY FOR A ROTATIONAL AMPLIFIER & G2 AMPL.
1514
ROTATIONAL AMPLIFIERS & G2 AMPL. CORRECTS PHASE OF INCOMING DATA TO PHASE OF MASTER CLOCK SO SAMPLING OF RECEIVED DATA POINTS OCCURS AT PROPER TIMES
1516

FIG. 27

CU

DIGITAL MODEM BLOCK DIAGRAM



CU MODEM

FIG. 28


DEMODULATOR
460
465
469
FILTER
Q
477
475
SIN
437
A/D
427
461
COS
FILTER
I
463
467
471
473
479

FIG. ~~26~~ 29


TO CPU 405 VIA DMA
SEED, Tss, R1, Ru/Cu
772
755
GAIN OUT TO RF SECTION 750
TO XTR
AGC
R/TNG
Ru/Cu
759
763
757
756
COEF
844
764
883
A/D
MF
DFE
ORTHO. CODE DEMUX
766
776
791
795
B
768
789A
790
789
G2
793
774
770
C<-T
765
788
FFE & ROT
769
802
834
767
SLCR
VD
836
800
M
852
F-1
858
854
856
850
846
838
821
832
831
833
LMS
DFE
820
824
842
830
TO CPU
COEF
792
TO CPU 405
1096
860
C3
862
ACC
CNTRL LOOP
798
781
806
782
794
CLOCK STEERING
822
904
760
761
754
906
900
882
FD
CLOCK
117
TO RU XMTR
784
VCXO
VCXO
808
LOCAL CARRIER REF
RF REF 4 Mhz
FREQ. SYN.
760
1092
1031
CAP DETECT
WINDOW
752
750
886
901
888
786
TIME BASE
787
M
796
FROM CPU
TO/FROM CIRCUITS & MEMORY NEEDING CONTROL/DATA
810
903
TO RU XMTR
RF SYNCH. DEMOD SECTION
758
F_0, F_4
GAIN IN FROM AGC 756
412
COAXIAL CABLE OR OTHER MEDIA
299
F_0, F_4 (Ru ONLY)
CPU
Ru/Cu
SYNCH. LOCAL OSC
1350
114.688/ 57.344 Mhz
CLKSRC-INT/ EXT/REMOTE
791
789
8.192 Mhz
405
CPU
CONTROL LOGIC
1082
762
TO FRAME DETECTOR
902
RU RECEIVER

FIG. 30


TO CPU 405
VIA DMA
SEED, Tss, R1, Ru/Cu
772
755
GAIN OUT
TO RF SECTION 750
TO XTR
AGC
759
R/TNG
763
757
Ru/Cu
756
COEF
844
764
883
A/D
MF
FFE
DFE
ORTHO.
CODE
DEMUX
766
776
791
795
B
768
789A
790
789
G2
793
774
770
C<-T
792
765
788
821
838
846
832
831
833
LMS
DFE
820
824
842
830
TO
CPU
COEF
792
TO CPU 405
1096
860
C3
862
ACC
858
F-1
854
856
850
VD
836
800
M
852
SLCR
FFE &
ROT
769
834
767
802
CNTRL LOOP
798
781
1086
Cu
PREAMBLE
760
761
754
906
908
FD
COEF
822
900
882
1092
782
794
784
VCXO
VCXO
808
FREQ. SYN.
4 MHz
760
752
750
MASTER
CLOCK FROM
CU XMTR
886
TIME BASE
PLL
786
793
M
796
FROM
CPU
TO/FROM CIRCUITS & MEMORY
NEEDING CONTROL/DATA
RF ASYNCH
DEMOD
SECTION
758
F0, F4
GAIN IN
FROM
AGC 756
299
F0, F4
CPU
Ru/Cu
1350
CLK SRC INT/
EXT/REMOTE
791
789
8.192
MHz
405
CPU
CONTROL
LOGIC
1082
762
CU
RECEIVER
COAXIAL
CABLE OR
OTHER MEDIA
SYNTHESIZED LOCAL MASTER CARRIER

FIG. 31


TRANSMISSION MEDIA
24
UP/DOWN CONVERTER
577
1082
405
CPU
CONTROL LOGIC
TO/FROM CIRCUITS NEEDING CONTROL/DATA
Td
RU / CU (LAT, HOP) SEED, TSS, R1
499'
499
506
533
532
508
518
524
522
509
T -> C
534
Tss
517R
517I
546R
527
549R
RU/CU COEF
558R
556
561
562R
557R
566
568R
576
572
574
SHAPING FILTER COEF
F
E
B
MUX
PRE
S
D/A
526
525
546I
544
549I
548
558I
560I
557I
563
564
562I
570
568I
M
399
514
520
516
PILOT CHANNEL DATA AND OTHER COMMAND & CONTROL CHANNEL DATA
SCRMBL
529
SEED
530
528
M
542R
542I
560R
PRECODE EQUAL FILTER
540
ACC
550
SEED
RNG
510
CONSTANT 13 BIT BARKER CODE
P DATA RU/CU
CU TRANSMITTER

FIG. 28A



FIG. 27 38



FIG. 28A


RGFIR
956
513
954
INTERVAL COUNTER
LD
ACQ
GAP_a
MF_PIPE[0]
902
922
943
974
EN
CLR
TIME_BASE
972
GAP_a
902
958
957
968
WIN_GEN
RGWR
13
980
978
970
RXRFSR
964
965
976
966
906
10
RE
910
914
904
IM
908
916
912
918
906
928
920
930
908
924
10
FIR
14
934
946
938
13
ACQ
RXRPAR
952
945
10
950
951
RXBRKR
942
932
13
NORM
15
944
1014
Z-2
1022
1018
926
940
936
948
1024
1026
CKRER
GRER
16
900
1020
1016
CHIP CLOCK
STEERING
TRACK ERROR
952
EN
CLR
FA_CNTR
RGFAR
960
1036
D
SHIFT_REG
1042
32
16
4
1038
16
EN
RSRH
+5V
16
1040
EN
RSRL
WATCH_DOG
902
CT-2 CLK
GAP_b
CKX2
RANGING
INFO
FRAME DETECTOR/
RANGING DETECTOR

FIG. 38


GAP ACQUISITION TIMING
ACTUAL GAP POSITION
END OF FRAME
962
990
NOISE PULSE
992A
BARKER CODE PULSE
FRAME 1
A
994
NOISE PULSE
992B
BARKER CODE PULSE
FRAME 2
B
962
996
NOISE PULSE
992C
FRAME 3
C
992D
FRAME 4
D
992E
FRAME 5
E
998
1000
FRAME 6
F
F
GAP_a
SAMPLE 1
SAMPLE 2
SAMPLE 3
SAMPLE 4&5
...
G
TØ
T1 T2 T3 T4 T5
T6
T7
NEW GAP_a

FIG. 39 35



36

FIG. ~~40~~



37

FIG. ~~41~~

FINE TUNING TO CENTER BARMER CODE



38

FIG. 27



FIG. 28B



FIG. 28C



FIG. 28D



42

FIG. 46



43

FIG. 47



FIG. 48



RU RANGING

FIG. 29



CU SIDE AUTHENTICATION WITH EDGE PULSES

FIG. 30



CU RANGING & CONTENTION RESOLUTION

~~RANGING AND CONTENTION RESOLUTION~~
~~CU SIDE~~

FIG. 31

41



CONTENTION RESOLUTION - RU
USING BINARY STACK

FIG. 33



RANGING - RU SIDE
BINARY TREE
ALGORITHM

FIG. 32

50
49



FIG. 37

50



FIG. 52

51



STATE MACHINE

FIG. 53

52



FIG. 45A
54A
53A



FIG. ~~45B~~ 54B
53B



FIG. ~~45C~~ 54C 53C


1166
FRAMING/ ADDRESSING/ PACKETIZATION CIRCUIT
BASEBAND DATA
1200
168
PAYLOAD DATA IN
HERALS/ E NETWORK/ NET/ LITE/ ULAR FACES
MASTER CLOCK
1176
1198
1194
CPU
MASTER CLOCK
PREAMBLE DATA
1196
1192
GAP MONITOR
1254
PAYLOAD DATA OUT
1252
1160
Cu MODEM
1170
ANY, CDMA, SCDMA, OR DMT TRANSMITTER
RF
UP/DOWN FREQ. CONVERTER
1174
MASTER CARRIER
CARRIER LOCAL OSCILLATOR MASTER
1178
1181
1195
1180
1172
SCDMA RECEIVER
UPSTREAM RF
DOWN-STREAM RF
HFC OR WIRELESS TRANSMISSION MEDIA
1162
UPSTREAM RF
1202
1228
1226
UP/DOWN FREQ. CONVERTER
1224
1204
CPU
1208
Td
1212
RF
RANGING GEN
1206
SCDMA TRANSMITTER
1220
1164
Ru MODEM
DOWN-STREAM RF
1190
1216
SCDMA/CDMA DMT RECEIVER
RECOVERED MASTER CLOCK
RECOVERED CARRIER
1214
PAYLOAD DATA OUT
PERIPHERALS ETC.
1218
M & C AND GAP ACQ DATA
1216
1210
SCDMA PAYLOAD DATA IN
TDMA, STDMA, F
INVERSE FOURIE
SCDMA, CDMA OR

FIG. 49

54



SIMPLE Cu SPREAD SPECTRUM RECEIVER

FIG. ~~50~~ 56

55



SIMPLE Ru SPREAD SPECTRUM TRANSMITTER

FIG. 5~~1~~ 5~~7~~ 56



SYNCHRONOUS TDMA SYSTEM

FIG. 54

57

OFFSET	1B ASIC		2A ASIC	
(Chips)	RGSRH	RGSRL	RGSRH	RGSRL
0	0x0000	0x8000	0x0001	0x0000
1/2	0x0000	0xC000	0x0001	0x8000
1	0x0000	0x4000	0x0000	0x8000
-1	0x0001	0x0000	0x0002	0x0000

FIG. 58

Training Algorithm



FIG. 59

Initial 2-Step Training Algorithm



2-STEP INITIAL EQUALIZATION TRAINING

FIG. 60

EQ Stability Check



Note: $Thrld_{coeff} = 7F00H$ $Thrld_{stable} = 10^{-3}$

FIG. 61

Periodic 2-Step Training Algorithm



Note:
1. For US, use PR instead of CE
2. The parameters are:

	DS	US
K1	30	30
K2	20	30
N	5	3
M	3	3

FIG. 62

RACM Correction



CONFIDENTIAL

Note: $Thrld_{amp} = TBD$

$Thrld_{phase} = TBD$

ROTATIONAL AMPLIFIER CORRECTION

FIG. 63

EQ Convergence Check



Note: $Thrld_{converge} = 10^{-5}$

CONFIDENTIAL

FIG. 64

Power Alignment Flow Chart



FIG. 65



FIG. 66



Total Turn Around (TTA) in frames = Offset

FIG. 67



FIG. 68

Figure 3-1: Frame start propagation along the channel



FIG. 69

Figure 69 Control message (downstream) and function (upstream) propagation in a 3 frames TTA channel



FIG. 70



Figure 3.4: Overall view of the CU sensing windows in a "boundless ranging" algorithm

FIG. 7I

Chip\FR	1	2	3	4	5	6	7		33
1	**0**	**0**	**1**	**0**	**0**	**1**	**1**	**...**	**0**
2	1	0	0	1	1	1	1	...	
3	0	0	0	1	1	1			
4	0	0	0	1	0	0	0	...	0
5	0	1	0	0	1				
6	0	0	1	1	1				
7	0	0	0	1	1				
8	0	0	0	0	1	0	0	...	

FIG. 72